

## MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

RECEIVED
By Carol Day at 2:49 pm, Nov 17, 2014

INTOX EC/IR II MAINTENANCE REPORT

שם	DAD	T	4	2

"Reference"				
		ive maintenance check (not to exceed 35		
		or repaired and whenever it is placed		
		s to the Breath Alcohol Program, DHSS.		
INTOX EC/IR II SN	NAME OF AGENCY	DATE OF INSPECTION		
12823	Pevely Police Department			
LOCATION OF INSTRUMENT (STREET AND CIT	<i>(</i> )	TIME OF INSPECTION		
401 Main Street Pevely		00:40 CDT		
CHECKLIST: Place a mark in the box	by each item if found to be s	satisfactory or is operating within		
	erved values where determined).	. Unmarked items must be corrected		
before using instrument.		5		
X DIAGNOSTIC RECORD				
X BLANK CHECK	X CO2 CH	HECK		
X FC 1 TEMP	X FLOW (	CHECK		
X SRC TEMP	X FCB CE	X FCB CHECK		
X DET TEMP		OMP CHECK		
X BT TEMP	<b>—</b>	AL CHECK		
X STD 2 TEMP	X PRINT	TEST		
X ETH CHECK				
BREATH ANALYZER ACCURACY STAND	ARDS			
SIMULATOR SOLUTION	X COMPRE	ESSED ETHANOL-GAS MIXTURE		
X STANDARD SUPPLIER into				
SIMULATOR TEMP (34°C +0.2°C	SIMULATOR S/N	SIMULATOR EXP DATE		
	SHOMION S, N			
ALL TRRAMERON OFFICER (ALLEGE)				
X CALIBRATION CHECK - (ONLY ON				
Run three tests using a star	dard solution. All three t	tests must be within $\pm 5\%$ of the standard valu	ıe	
Run three tests using a star and must have a spread of .0	dard solution. All three t		ıe	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED)	dard solution. All three t 05 or less. Mark the box o	tests must be within $\pm 5\%$ of the standard valucorresponding to the standard solution being	ıe	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST REAL	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105%	tests must be within ±5% of the standard valucorresponding to the standard solution being	ıe	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084%	tests must be within ±5% of the standard valu corresponding to the standard solution being INCLUSIVE INCLUSIVE	ıe	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105%	tests must be within ±5% of the standard valu corresponding to the standard solution being INCLUSIVE INCLUSIVE	ıe	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%	tests must be within ±5% of the standard valu corresponding to the standard solution being INCLUSIVE INCLUSIVE INCLUSIVE	ie	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084%	tests must be within ±5% of the standard valu corresponding to the standard solution being INCLUSIVE INCLUSIVE	ıe	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%	tests must be within ±5% of the standard valu corresponding to the standard solution being INCLUSIVE INCLUSIVE INCLUSIVE	ie	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANG	tests must be within ±5% of the standard valucorresponding to the standard solution being  INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:	ıe	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE 0.0509 0 .1014	tests must be within ±5% of the standard value corresponding to the standard solution being  INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0	1e	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE CONTRACTOR OF MODIFICATION THAT WAS METATION OF MODIFICATION OF MODIFICATION OF MODIFICATION THAT WAS METATION OF MODIFICATION OF MODIFICATIO	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE	ıe	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE CONTRACTOR OF MODIFICATION THAT WAS METATION OF MODIFICATION OF MODIFICATION OF MODIFICATION THAT WAS METATION OF MODIFICATION OF MODIFICATIO	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE	le	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY ALL SATISFACTORILY AND WITHIN ESTABLISHED 1	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF THE POLICY	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE	ie	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12 LIST ANY NEW PARTS AND DESCRIBE ANY ALT	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF THE POLICY	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE	ae	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY ALL SATISFACTORILY AND WITHIN ESTABLISHED 1	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF THE POLICY	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE	ae	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY ALL SATISFACTORILY AND WITHIN ESTABLISHED 1	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF THE POLICY	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE	ae	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED INSTRUMENT OPERATING ACCORDING	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF THE POLICY	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE  Y).	ae .	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED INSTRUMENT OPERATING ACCORDING	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF 1014  TESTS IN THE FOLLOWING RANGE OF 1014  TESTS IN THE SIDE IF NECESSARY  TO DHSS SPECIFICATIONS	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE  Y).	ae	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED INSTRUMENT OPERATING ACCORDING	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF 1014  TESTS IN THE FOLLOWING RANGE OF 1014  TESTS IN THE SIDE IF NECESSARY  TO DHSS SPECIFICATIONS	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE  Y).	ae	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED INSTRUMENT OPERATING ACCORDING INSPECTING OFFICER  SIGNATURE	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF 1014  TESTS IN THE FOLLOWING RANGE OF 1014  TESTS IN THE SIDE IF NECESSARY  TO DHSS SPECIFICATIONS	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE  Y).  L NAME ALL, BENJAMIN	ue .	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED INSTRUMENT OPERATING ACCORDING INSTRUMENT OPERATING ACCORDING INSPECTING OFFICER  SIGNATURE  TYPE II PERMITNIMBER EXPIRE	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF THE STATE OF	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE  Y).  L NAME ALL, BENJAMIN	ue	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY ALL SATISFACTORILY AND WITHIN ESTABLISHED INSTRUMENT OPERATING ACCORDING INSTRUMENT OPERATING ACCORDING SIGNATURE  TYPE II PERMIN NUMBER EXPIR 240293 06/	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF THE STATION OF MODIFICATION THAT WAS MUST USE OTHER SIDE IF NECESSARY TO DHSS SPECIFICATIONS  PRINT FOLL LITTERAL TELEPHONE (636) 4	tests must be within ±5% of the standard value corresponding to the standard solution being INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE  Y).  L NAME ALL, BENJAMIN NUMBER	e .	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED INSTRUMENT OPERATING ACCORDING INSPECTING OFFICER  SIGNATURE  TYPE II PERMIT NUMBER EXPIR 240293 06/	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE OF THE STREET	tests must be within ±5% of the standard value corresponding to the standard solution being  INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE  Y).  L NAME ALL, BENJAMIN NUMBER 475-5301	e .	
Run three tests using a star and must have a spread of .0 used. (PRINTOUT ATTACHED)  X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 0.099 g/210L  INDICATE THE NUMBER OF BREATH  REFUSALS 0 004 12  LIST ANY NEW PARTS AND DESCRIBE ANY ALL SATISFACTORILY AND WITHIN ESTABLISHED INSTRUMENT OPERATING ACCORDING INSTRUMENT OPERATING ACCORDING SIGNATURE  TYPE II PERMIN NUMBER EXPIR 240293 06/	dard solution. All three to 05 or less. Mark the box of BETWEEN 0.095% AND 0.105% BETWEEN 0.076% AND 0.084% BETWEEN 0.038% AND 0.042%  TEST 2 0.099 g/210L  TESTS IN THE FOLLOWING RANGE AND 0.0509 0 .1014  TERRATION OR MODIFICATION THAT WAS MADE IN THE SIDE IF NECESSARY TO DHSS SPECIFICATIONS  PRINT FULL LITTERA TELEPHONE (636) 4  FO THE:  souri Department of Heal	tests must be within ±5% of the standard value corresponding to the standard solution being  INCLUSIVE INCLUSIVE INCLUSIVE  TEST 3 0.098 g/210L  GES SINCE THE LAST MAINTENANCE REPORT:  0 .1519 1 OVER .19 0  MADE TO RESTORE THE INSTRUMENT TO OPERATE  Y).  L NAME ALL, BENJAMIN NUMBER 475-5301  Lth and Senior Services,	ae .	